

TEVO-NV4K comes with an Ultra-HD imaging system, Rally delivers brilliantly sharp video, outstanding color, and exceptional optical accuracy at resolutions up to 4K. This camera adopts 1/2.7 inch HD Color CMOS, 8.29 effective mage pixel, 138° super-wide field of view, to emphasize faces and render natural-looking skin tones, even in dim or backlit conditions. NV4K meets with the application for Ultra HD recording and streaming, video conferencing, and broadcasting that supports USB cameras.

Key Features

- Fixed focus Pan Tilt Camera
- Sleek and intelligent design
- Plug & Play USB Connectivity
- Crystal clear HD1080P image quality
- Accurate, smooth and silent PTZ Movement
- Preset: 9 via IR remote setting (255 via RS232)
- Superior quality with Full Glass Lens Material
- 138° wide field of view with no video distortion
- 1/2.7 inch high quality, 8.29 MEGA PIXEL (16:9) CMOS sensor
- Support ceiling mount, wall mount and tripod mount (Reverse mountable)
- 2D and 3D NR for best video quality in different lighting conditions
- Support Visca, Pelco-P, and Pelco-D protocol, RS232/RS485 Camera Control
- Compatible with all popular applications and cloud systems:



More Details



ACCURATE, SMOOTH AND SILENT PTZ MOVEMENT

Along with 350 degree pan & 90 degree tilt rotation at adjustable speed and fast & accurate focus to capture any view in conferencing space.



AS EASY AS PLUG AND PLAY

Video output: USB2.0 Plug and play, Anyone can easily setup this USB Camera and control conferencing/ Live Streaming.

SUPERIOR QUALITY FULL GLASS LENS

with an Ultra-HD imaging system, Rally delivers brilliantly sharp video, and exceptional optical accuracy at resolutions up to 4K. This camera adopts 1/2.7 inch HD Color CMOS & 8.29 effective mage pixel



FIXED FOCUS PAN TILT 138° FOV

Fixed focus pan tilt camera, 138° wide field of view with no video distortion



MULTIPLE INSTALLATIONS

Support multiple mount way: available to install on desk, monitor, wall, tripod or up-side down in-ceiling.



COMPATIBLE WITH MAC® AND PC

Simply connect a PC or Mac® to conduct a meetings within the user's own familiar computing environment. Compatible with Mac and PC. System Requirements: Windows 7, 8.1 or 10, Mac OS X 10.7 or higher, Android, Linux.



Product Specifications

Model No	TEVO-NV4K
Image Sensor	1/2.7 inch HD Color CMOS
Effective pixel	8.29 mega pixel (16: 9)
Horizontal Resolution	4K (3840 x 2160), 2K (2560*1440), 1080P (1920*1080)
Lens	Fixed focus 2.1mm wide angle lens
Signal standard	NTSC/PAL
SNR ratio	≥50.dB
Field of View	Fixed focus, 138°
Control terminal	RS-232, RS485
Pan movement range	Pan: ±175°(max speed 80°/S)
Tilt movement range	Tilt: -35°~ + 55°(max speed 60°/S)
Preset position	IR-Remote supports 9 presets, PELCO Control Protocol supports 255 presets
Control Protocol	VISCA, PELCO-D, PELCO-P (RS-232, RS485)

HD Video output	USB
Work Temperature	-10°~50°
Work Humidity	-20°~60°
Baud rate	38400/9600bps
Decoder	Built-in
Address Set	1~64
Installation	Support desktop, Tripod, Wall mount and Ceiling mount
Power supply	DC 12V/2A
Power	12W
Weight	1.5kg/2.85g(before / after packing)
Size	182*182*182mm/262*233*220(before / after packing)
Accessories	DC 12V Power adaptor, IR remote control, Ceiling brackets & screws, Manual, USB cable

Connection

Include Ceiling Mount

